



Ultracore 500 SPC

LUXURY SPC
FLOORING

NEW
HORIZONS

HERRINGBONE



INCO

ULTRACORE 500 SPC

HERRINGBONE

Wear Layer 0.3 mm
Thickness (4.0 mm core + 1.0 mm IXPE) 5.0 mm
Size 610 mm x 122 mm
24 pieces/box 1.61 sqm



TV 5530 SHR Willow Oak **NEW**



TV 5531 SHR Desert Oak **NEW**



TV 5527 SHR Harvest Oak **NEW**



TV 5528 SHR Autumn Cherry **NEW**



TV 5532 SHR Saddle Oak **NEW**



TV 5529 SHR Nutmeg Oak **NEW**

ULTRACORE 500 SPC

HERRINGBONE 

Wear Layer 0.3 mm
Thickness (4.0 mm core + 1.0 mm IXPE) 5.0 mm
Size 610 mm x 122 mm
24 pieces/box 1.61 sqm



TV 5530 SHR Willow Oak **NEW**



TV 5531 SHR Desert Oak **NEW**



TV 5527 SHR Harvest Oak **NEW**



TV 5528 SHR Autumn Cherry **NEW**



TV 5532 SHR Saddle Oak **NEW**



TV 5529 SHR Nutmeg Oak **NEW**

Technical Data

PROPERTY	TEST METHOD	ULTRACORE 500 HERRINGBONE
Thickness of Wear Layer	ASTM F410-08 [2013], GB/T 4085-2015	Fv = 2.9 mm ³
Residual Indentation	ASTM F1914-07 [2011]	≤ 0.02 mm
Dimension Stability	ASTM F2199-09 [2014], ASTM F2199	≤ ±0.15%
Staining and Resistance to Chemical	ASTM F925-13, EN ISO 26987:2012	Not Detected
Resistance to Heat	ASTM F1514-03 [2013], GB/T 4085-2015	0 mm
Resistance to Light	ASTM F1515-15, GB/T 8427-2008	Grade (Bluewood std) 6
Castor Chair Resistance	EN 425 / ISO 4918, GB/T 4085-2015	25000 cycles
Fungi Resistance	ASTM G21-15, GB/T 24128-2018	Grade 0
Formaldehyde Content	ASTM D6007-14, GB/T 39600-2021 / GB/T 17657-2013	Not Detected
Impact Resistance	DIN 51130:2014, ASTM E492-09	IIC61
Slip Resistance	DIN 51139:2014	dry: 0.69; wet: 0.72
Fire-Resistant	EN 13501-1, EN 14041:2008	Bfl-S1
Soundproof	ASTM E492-09	IIC61

PRODUCED UNDER HIGH QUALITY SUPERVISION WITH **ISO 9001 ISO 14001 OHSAS 18001 CE STDS.**



CLICK
SYSTEM



100%
WATERPROOF



EASY TO CLEAN
& MAINTAIN



ANTI
BACTERIAL



0.3mm
WEAR LAYER



TERMITE
PROOF



SIMPLE & QUICK
TO INSTALL

✓ TRUETOUGH TECHNOLOGY

Brings natural feel and texture to life.

✓ COREPROTECT TECHNOLOGY

Ensures durability for long-lasting performance.



Scan to contact us
on WhatsApp

