

TACO

ECOFLOORING

Super SPC with **IXPE System**



5
mm

WOOD SERIES

Wear Layer **0.3 mm**
Thickness **5.0 mm**
(1mm IXPE Underlayment)

Size **172 mm x 1210 mm**
11 pieces/box **2.29 sqm**

**CLICK
SYSTEM**



EV 5001 SPC Snow Ash



EV 5003 SPC Smoke Elm



EV 5002 SPC Blonde Maple



EV 5009 SPC Sunrise Beech



EV 5006 SPC Washed Walnut

WOOD SERIES

Wear Layer **0.3 mm**
Thickness **5.0 mm**
(1mm IXPE Underlayment)

Size **172 mm x 1210 mm**
11 pieces/box **2.29 sqm**

**CLICK
SYSTEM**



EV 5006 SPC Washed Walnut



EV 5004 SPC Summer Oak



EV 5010 SPC Earthy Oak



EV 5005 SPC Spiced Walnut

STONE SERIES

Wear Layer **0.3 mm**
Thickness **5.0 mm**
(1mm IXPE Underlayment)

Size **300 mm x 600 mm**
12 pieces/box **2.16 sqm**

**CLICK
SYSTEM**



EV 5007 SPC Pebble Hill



EV 5008 SPC Iron Harbor

Technical Data

CHARACTERISTICS	TEST METHOD	PASS
Thickness Tolerance	ISO 24337	✓
Squareness	ISO 24337	✓
Residual Indentation	EN ISO 24343	✓
Dimension Stability	ISO 23999	✓
Resistance to Chemical	ASTM F-925-12	✓
Thickness Swelling	ISO 24336	✓
Peel Strenght	ISO 24345	✓
Cross-Cut	EN ISO 2409	✓
Scratch Resistance	ISO 1518	✓
Micro-Scratch Resistance	EN ISO 16094	✓
Abrasion Test	EN ISO 660	✓



MOTIF ALAMI & VARIATIF



ANTI RAYAP



INSTALASI MUDAH & CEPAT



TAHAN AIR



TAHAN LAMA & MUDAH DIRAWAT