

***ECO*FLOORING**

Super SPC with **IXPE System**



5
mm

WOOD SERIES

Wear Layer 0.3 mm
Thickness 5.0 mm
 (1mm IXPE Underlayment)

Size 172 mm x 1210 mm
11 pieces/box 2.29 sqm

CLICK
SYSTEM



EV 5001 SPC Snow Ash



EV 5003 SPC Smoke Elm



EV 5002 SPC Blonde Maple



EV 5009 SPC Sunrise Beech



EV 5006 SPC Washed Walnut

WOOD SERIES

Wear Layer **0.3 mm**
Thickness **5.0 mm**
(1mm IXPE Underlayment)

Size **172 mm x 1210 mm**
11 pieces/box **2.29 sqm**

CLICK
SYSTEM



EV 5006 SPC Washed Walnut



EV 5004 SPC Summer Oak



EV 5010 SPC Earthy Oak



EV 5005 SPC Spiced Walnut

STONE SERIES

Wear Layer **0.3 mm**
Thickness **5.0 mm**
(1mm IXPE Underlayment)

Size **300 mm x 600 mm**
12 pieces/box **2.16 sqm**

CLICK
SYSTEM



EV 5007 SPC Pebble Hill



EV 5008 SPC Iron Harbor

Technical Data

CHARACTERISTICS	TEST METHOD	PASS
Thickness Tolerance	ISO 24337	✓
Squareness	ISO 24337	✓
Residual Indentation	EN ISO 24343	✓
Dimension Stability	ISO 23999	✓
Resistance to Chemical	ASTM F-925-12	✓
Thickness Swelling	ISO 24336	✓
Peel Strenght	ISO 24345	✓
Cross-Cut	EN ISO 2409	✓
Scratch Resistance	ISO 1518	✓
Micro-Scratch Resistance	EN ISO 16094	✓
Abrasion Test	EN ISO 660	✓



MOTIF ALAMI & VARIATIF



ANTI RAYAP



INSTALASI MUDAH & CEPAT



TAHAN AIR



TAHAN LAMA & MUDAH DIRAWAT



Scan to contact us
on WhatsApp

